



GENIUS iTouch Series cont.

PART #	MODEL	DESCRIPTION
E53-4930	2004/10K	UP TO 10 PROBES BASE MODEL UP TO 16 PROBES** DELUXE MODEL ** REQUIRES USE OF MULTI-FUNCTION 8 INPUT X1399 BOARD INCLUDED WITH DELUXE MODEL
NOTE: UP TO 30 PROBES ARE POSSIBLE WITH OPTIONAL BOARDS & MULTIPLE ZONES ** CALL EXACON FOR DETAILS**		
E53-5402	T15-WD	SAFETY OVER-RIDE - RECOMMEND 4 PER ZONE
E53-4670	RH-3	HUMIDITY PROBE - UP TO 2 WITH BASE MODEL - UP TO 4 WITH DELUXE MODEL
E53-4677	CRH-3/MGCB	RED WIRE HARNESS - 1 REQD PER HUMIDITY PROBE
E53-9055	750JLPRS	WATER METER W/PULSE COUNT (3/4" CONNECTION) 4 CAN BE CONNECTED TO BASE MODEL 4-12* CAN BE CONNECTED TO DELUXE MODEL * REQUIRES USE OF MULTI-FUNCTION INPUT X1399 BOARD (INCLUDED IN DELUXE MODEL)
E53-9287	GEV4-S4	LIGHT OR VARIABLE SPEED MODULE (4 OUTPUTS FOR 15AMPS) UP TO 2 GE-V4/S CAN BE CONNECTED TO DELUXE MODEL BASE MODEL REQUIRES OPTIONAL BOARD X1201 FOR LIGHT OPTION
E53-9775	GE-V1	MODULE - 1 STAGE 10 AMP BOOSTER (1 OR 2)
E53-9780	GE-V2	MODULE - 2 STAGE 10 AMP EACH BOOSTER (1 OR 2)
E53-9895	GE-SP1	STATIC PRESSURE PROBE - UP TO 2 WITH BASE MODEL - UP TO 4 WITH DELUXE MODEL
E53-9794	GE-MS10	0-10V MODULE C/W RELAYS FOR TWO 0-10V HEATER OR VARIABLE FANS. - UP TO 2 ON DELUXE MODEL - BASE MODEL REQUIRES X1276 BOARD FOR 2
E53-9898A	CSD-1A	CURRENT SENSOR FOR DURATION COUNTER UP TO 4 ON BASE MODEL, UP TO 6-12* ON DELUXE MODEL
NOTE: REQUIRES USE OF MULTI-FUNCTION 8 INPUT X1399 INCLUDED WITH DELUXE MODEL FOR 7-12		

BIRD WEIGHING OPTIONS

PART #	MODEL	DESCRIPTION
E53-9510	OPTI-GAINKIT	LOAD CELL AND PLATFORM KIT FOR BROILERS
E53-9512	OPTI-GAIN-1	OPTIGAIN LOAD CELL MODULE WITHOUT PLATFORM
E53-9502	OPTI-GAINKIT/D	OPTIGAIN TURKEY LOAD CELL AND PLATFORM
UP TO 4 OPTIGAIN LOAD CELL/KIT CAN BE CONNECTED TO THE DELUXE MODEL BASE MODEL MUST HAVE THE OPTIONAL X1276 FOR BIRD WEIGHING OPTION		
E53-9517	OPTIGAINBP/KIT	PERCH SCALE FOR LAYERS

FEED BIN SCALES

BASE MODEL CAN OPERATE UP TO TWO BIN SCALES, DELUXE MODEL CAN OPERATE UP TO 4 BIN SCALES

PART #	MODEL	DESCRIPTION
E53-9610SB	FBT-SB	FEED BIN TRANSMITTER - 1 PER BIN REQUIRED
E53-9611	GE-LIM	LIGHTNING ISOLATOR - 1 PER BIN REQUIRED
E53-9615	SB-15K/KIT	SHEAR BEAM LOAD CELL C/W SUPPORT - 1 PER LEG (6 MAX /BIN, 6MT MAX LOAD PER LEG)
E53-9898A	CSD-1A	CURRENT SENSOR - 1 PER BIN AUGER
E53-9614	SB-15K	SHEAR BEAM LOAD CELL ONLY (6MT)

WEATHER STATION

PART #	MODEL	DESCRIPTION
E53-9530	MSTAT-1	WEATHER STATION KIT INCLUDES RAIN DETECTOR, WIND DIRECTION AND SPEED, SUPPORT AND ELECTRONIC NETWORK CARD X1406